

1. CONDUCTOR:

- 1.1 Size and Material: 16 7/.0192" AWG tin-plated copper wire.
- 1.2 O.D.: .058" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .118" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:


- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C

4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 3134.
- 4.2 CSA standard C22.2 No.210 (AWM), Class I Group A.

CUSTOMER APPROVAL

Sign: _____
 Date: _____

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com					
								Date: June 14, 2017							
								Verified: <i>Carrie Holt</i>		Description: XSR30Z167/0192-X					
								Date: June 14, 2017							
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								Size: A		Scale: ---		Page: 1 of 1		Code Ident. No: 57104	Specification No.: Q04263-X