



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 6/2/2017
Issue: 2

Construction

| Description: 2/C 8 AWG (133) BC TXL/TPV OAFS + Drain Wire | | Diam. (In) |
|--|---|-------------------|
| Component: | 2 Conductors Twisted | |
| Conductor: | 8 AWG (133) Stranded Bare Copper Conductor | 0.1693" |
| Insulation: | 0.022" XLPE to SAE J-1128 Type TXL | 0.2133" |
| Color Code: | Red + Gray | 0.2133" |
| Cable Assembly: | 2 Conductors Twisted (Cabled) 3 twists per foot | 0.427" |
| Fillers | Fibrillated polypropylene or solid fillers for roundness (optional) | 0.427" |
| Drain Wire: | 12 65/30 TC RB | 0.427" |
| Shield: | Aluminum Mylar Foil Shield | 0.43" |
| Tape: | Non-Woven Separator Tape for Strip-Ability (optional) | 0.43" |
| Jacket: | 0.050" Santoprene TPV | 0.53" |
| Jacket Color: | Black | 0.53" |

Print:

Specifications:

 Temperature Rating: -40°C to +125°C

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170206