



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 6/8/2017
Issue: 1

Construction

| Description: 2/C 12 19/25 TXL/TPV OAFS + Drain | | Diam. (In) |
|---|---|-------------------|
| Component: | 2 Conductors Twisted | |
| Conductor: | 12 AWG 19/.0185" Bare Copper to ASTM B 8-77 | 0.09" |
| Insulation: | 0.016" XLPE to SAE J-1128 Type TXL | 0.122" |
| Color Code: | Yellow/Gray + Dark Blue | 0.122" |
| Cable Assembly: | 2 Conductors Twisted (Cabled) 4 Twists per foot | 0.214" |
| Fillers | Fibrillated polypropylene or solid fillers for roundness (optional) | 0.214" |
| Drain Wire: | 18 7/26 TC | 0.214" |
| Shield: | Aluminum Mylar Foil Shield | 0.217" |
| Tape: | Non-Woven Separator Tape for Strip-Ability (optional) | 0.217" |
| Jacket: | 0.045" Santoprene TPV | 0.307" |
| Jacket Color: | Black | 0.307" |

Print:

Specifications:
Temperature Rating: -40°C to +125°C

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170205



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 6/8/2017

Issue: 1

Drawing/Rotation:

IQ170205