

**ALPHA WIRE**

Part Number: 17-1648

Issue:

Page 1 of 1 Pages

Issue Date:

6/8/2017

**Cable Specification**

**Component 1**                    5 PAIR  
Conductor: 22 (7/30) AWG TC  
Insulation: 0.010" Wall, Nom. SR-PVC  
Color Code: 10 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED  
Pair: 2/Cond Cabled Together

**Final Assembly**                5 Components  
Core Wrap: NWP Tape, 25% Overlap, Min.  
Shield: AM Foil Tape, 25% Overlap, Min.  
Drain Wire: 22 (7/30) AWG TC  
Jacket: 0.032" Wall, Nom., PU  
Jacket OD: 0.295"  
Jacket Color: YELLOW

**Approvals**

UL: AWM/STYLE 20668  
VW-1  
CSA: AWM I/II A/B  
FT1  
MIL: NONE  
CE Compliant: YES  
ROHS Compliant: YES  
REACH Compliant: YES

**Miscellaneous**

Temperature: 90 C  
Voltage: 300 V<sub>RMS</sub>  
Put Ups: 1000 FT PUTUP  
Requested Quantity: 5000Ft.

**Application Notes**

5 pr 25485 YL except Color code as

1. Red-Black
2. White-Green
3. Blue-Gray
4. Purple-Yellow
5. Orange-Brown

CUSTOM PRODUCTS ARE NON-CANCELLABLE &amp; NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

**PROPRIETARY NOTICE**

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.