	A B C	
	ESTIMATED CORD WEIGHT: 81lbs/1000'	
1	\$\overline{\phi_{0.403}}{\phi_{0.403}}	1
2	FILLER TO MAINTAIN ROUNDNESS 20awg WIRES TO BE SHIELDED FROM 18awg WIRES	2
3	SPECS: - Minimum 300V RMS - Minimum 105C - UL Listed / CSA Certified - White TPE Jacket w/filler to maintain roundness - 18awg - White - copper stranded - 18awg - Black - copper stranded - 18awg - Green - copper stranded - 20awg - Greyt - copper stranded - shielded - 20awg - Greyt - copper stranded - shielded - 20awg - Greyt - copper stranded - shielded - *Purple and Grey to be shielded from White/Black/Green - RoHS Compliant ORDER REQUIREMENTS: - To be supplied on 1000' spools - Spool to bayye 1-3/4" center hole	3
4	- Spool to have 1-3/4" center hole - Spool to be wrapped to prevent damage or marring of outer jacket during transport - Spool to be clearly marked with: - OCL part number - Vendor part number - Listing (UL/CSA) File number - Listing (UL/CSA) File number - Listing (UL/CSA) File number - Description: CORD 5-WIRE WHITE - LINE VOLTAGE - TPE Description: CORD 5-WIRE WHITE - LINE VOLTAGE - TPE Description: Description: Cord 5-WIRE WHITE - LINE VOLTAGE - TPE Description: Cord 5-WIRE WHITE - LINE VOLTAGE - TPE Description: Description: Cord 5-WIRE WHITE - LINE VOLTAGE - TPE Description: Description: Cord 5-WIRE WHITE - LINE VOLTAGE - TPE Description: Descrip	4
	ARCHIECTURAL LIghting Control of	