



Specification Sheet

Lake Cable Part #: S204T26/PU

Description: 20 AWG 4 conductors stranded tinned copper wire with PVC insulation and a pressure extruded TPU jacket.

- 1. Conductor**
 - 1.1. AWG Size & Stranding: 20 AWG 26 Strands Class M
 - 1.2. Material: Annealed Tinned Copper
 - 1.3. Conductor Count: 4 Conductors
- 2. Insulation**
 - 2.1. Material: Polyvinylchloride
 - 2.2. Wall Thickness: 0.010"
 - 2.3. Color Code: Black, White, Blue, Brown
- 3. Cable Assembly**
 - 3.1. Lay Length: 1.50" LHL (8.0 tw/ft), Nominal
 - 3.2. Separator: Tissue Paper
- 4. Jacket**
 - 4.1. Material: Pressure Extruded Polyurethane
 - 4.2. Wall Thickness: 0.030"
 - 4.3. Diameter: 0.210" ± .005"
 - 4.4. Color: Black
 - 4.5. Ripcord: N/A
 - 4.6. Weight: 28 Lbs/Mft
- 5. Markings**
 - 5.1. Type: N/A
 - 5.2. Legend: N/A
 - 5.3. Footage Markers: N/A
- 6. Standards**
 - 6.1. No Agency Approvals
 - 6.2. Operating Temperature: -40°C to 90°C
 - 6.3. Operating Voltage: 300V RMS Maximum
 - 6.4. All materials used in the manufacturing of this cable are RoHS II compliant
 - 6.5. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION