

[Flexible Wiring Conduits](#) > [Liquid-Tight Flexible Conduit](#) > [Sealtite® Metallic Unlisted](#) > [Type EF - General Construction Grade Liquid-Tight Flexible Metal Conduit \(LFMC\)](#) > Item # 39413

Item # 39413, Type EF - General Construction Grade Liquid-Tight Flexible Metal Conduit (LFMC)

[Request Information](#)

[Printable Page](#)

[Download PDF](#)

[Email This Page](#)



Thermoplastic PVC jacket no bonding wire

Conduit shall be Anaconda SEALTITE® Type EF. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked hot dipped zinc galvanized steel core with sunlight resistant PVC outer jacket. Type EF conduit shall be used for applications where agency approvals are not required. Conduit IP 67 rated when installed with approved end connectors.

DOWNLOADS

[Packaging, Cutting Instructions, Custom Cut Lengths](#)

[Chemical Resistance Chart](#)

[Type EF Datasheet](#)

[1/2" EF MSDS](#)

[Specifications](#) | [Installation](#) | [Application](#)

Specifications	
Type	EF
Electrical Trade Size	1/2 in 16 mm
Length	1000 ft 304.8 m
Packaging	Standard Reels
Inside Diameter	0.620 to 0.640 in 15.748 to 16.256 mm
Outside Diameter	0.820 to 0.840 in 20.828 to 21.336 mm
Approx. Inside Bend Radius	2.5 in 63.5 mm
Approx. Weight per 100 ft	19 lbs 8.62 kg
Color	Gray
Note	Standard SEALTITE® Type EFST is recommended in sizes above 2"
Certifications	RoHS WEEE
Cross-Reference #	80114 EF-11 EFLT EFLT-1/2 EXLT

EXLT-1/2

Installation

- Conduit used with standard liquid-tight connector for easy installation. IP 67 Rated when installed with approved connectors.
- Delivers superior wiring protection where agency approvals are not required.
- Manufactured in a full range of trade sizes from 3/8" through 2".
- Smooth appearing jacket for exposed applications.
- Rated for temperature range of -4°F to +176°F (20°C to +80°C).
- Provides liquid-tight raceway for electrical conductors.

Application

Designed for General Construction Grade Applications
 Temperature Range: -4°F to +140°F (-20°C to +60°C)

HIGH QUALITY CONDUIT FOR A WIDE RANGE APPLICATIONS

Anamet Electrical, Inc. is the leading worldwide supplier of SEALTITE® flexible wiring conduit. We are known for our high quality wiring conduits used in applications ranging from machine tools, computer wiring, office furniture, nuclear power plants, mass-transit vehicles, military shielding and industrial construction.

ANACONDA SEALTITE® LIQUID-TIGHT FLEXIBLE CONDUIT

FLEXIBLE METALLIC CONDUIT

INDUSTRIAL STRIPWOUND HOSE

FITTINGS

FIRETECH™ HIGH TEMPERATURE ACCESSORIES

Sealtite® Metallic Listed
 Sealtite® Metallic Unlisted
 Sealtite® Non-Metallic Listed
 Specialty

Listed
 Recognized
 Unlisted

Square-locked
 Fully Interlocked

Stainless Steel Liquid-Tight Connectors
 NMUA Connectors
 Nickel Plated Brass Compact Fittings NPT
 Nickel Plated Brass Compact Fittings ISO
 Steel Sealtite fittings

FireTech™ Sleeve
 FireTech™ Wrap
 FireTech™ Tape
 FireTech™ Sheet



MAIL US
 Anamet Electrical, Inc.
 1000 Broadway Ave. East
 PO Box 39
 Mattoon, IL 61938

TALK TO US
 Call: (800) 230-3718
CONTACT US
 Fax: (800) 677-2706

REACH OUT TO US
[Email](#)

ON THE WEB
www.anacondasealtite.com

FOLLOW US

CERTIFICATES



ASSOCIATIONS



[Privacy Policy](#) | [Sitemap](#) | [Catalog Index](#)

© 2015, Anamet Electrical, Inc. | Site created by [Thomas Web Solutions](#) and powered by [Navigator Platform](#)