



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: SVT 18/3 41SBC 105* Paper

STOCK NUMBER: 56-46-16-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .260" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .079" in.
NOMINAL WALL THICKNESS: .015" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 18 AWG 41X.0063" SBC

TEMPERATURE:

105°C - max
-20°C - min

FILLERS:

PAPERFILLER

PRINT:

INDENT

(UL) VW-1 E46194 (M) SVT 3/C 18 AWG (0.82mm²) 105°C 300V (CSA) FT1,FT2 LL90458(M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013