



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 16-26 3/C SJTOW Paper 105\* 300V

**STOCK NUMBER:** 56-59-24-01

**JACKET:**

<b>NOMINAL OUTSIDE DIAMETER:</b>	.345"	in.
<b>NOMINAL WALL THICKNESS:</b>	.037"	in.
<b>COMPOUND:</b>	Polyvinyl Chloride	

**CONDUCTOR:**

<b>NUMBER OF CONDUCTORS:</b>	3	
<b>NOMINAL OUTSIDE DIAMETER:</b>	.120"	in.
<b>NOMINAL WALL THICKNESS:</b>	.030"	in.
<b>INSULATION COMPOUND:</b>	Polyvinyl Chloride	
<b>COPPER:</b>	16 AWG 26X.010" SBC	

**TEMPERATURE:** 105\*

**FILLERS:** Paperfiller

**PRINT:**

**INDENT**  
(UL) VW-1 E46194 (M) SJTOW 3/C 16 AWG (1.31mm<sup>2</sup>) 105°C DRY 60°C WATER RESISTANT  
300V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013