



# Specification Sheet

## Lake Cable Part #: VXC102T

**Description:** 10 AWG 2 conductor 7 strand tinned copper with XLPE insulation, unshielded with an overall CPE jacket 600V control tray cable, approved for use in SUN RES DIR BUR OIL RES I & II 90°C applications.

### 1. Conductor

- 1.1. AWG Size & Stranding: 10 AWG 7 Strands Class B
- 1.2. Material: Annealed Tinned Copper
- 1.3. Conductor Count: 2 Conductors

### 2. Insulation

- 2.1. Material: Cross-linked Polyethylene
- 2.2. Wall Thickness: 0.030"
- 2.3. Color Code: Method 1, Table E-2

### 3. Assembly

- 3.1. Lay Length: 5.25" LHL
- 3.2. Fillers: Non-Hygroscopic Polypropylene - As required for a circular cross-section
- 3.3. Binder: Clear Mylar

### 4. Jacket

- 4.1. Material: Chlorinated Polyethylene
- 4.2. Wall Thickness: 0.045"
- 4.3. Diameter: 0.443" +/- 0.035"
- 4.4. Color: Black
- 4.5. Ripcord: Yes
- 4.6. Cold Bend Rating: -25°C
- 4.7. Weight: 135 lbs./Mft.

### 5. Markings

- 5.1. Type: Cable shall be permanently identified via surface inkjet print
- 5.2. Legend: LAKE CABLE E208309 10AWG 2C (UL) TC XHHW-2/VW-1 600V 90°C DRY/WET CPE JACKET SUN RES DIR BUR OIL RES I & II FT4 "ROHS II" MADE IN USA
- 5.3. Footage Markers: Yes

### 6. Standards

- 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
- 6.2. Cable is suitable for use in Class I Division 2 hazardous locations
- 6.3. Individual conductors pass UL VW-1 flame test, rated XHHW-2/VW-1
- 6.4. UL listed as Type TC per UL Standard 1277 for tray cables
- 6.5. UL approved for Direct Burial, Sunlight and Oil I & II Resistant applications
- 6.6. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- 6.7. Meets ICEA S-73-532, where applicable
- 6.8. All materials used in the manufacture of this cable are RoHS II & REACH compliant
- 6.9. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

---

Signature

---

Company

---

Date

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**