

**1. CONDUCTOR:**

- 1.1 Size and Material: 10 37/26 AWG silver-plated copper wire.
- 1.2 O.D.: .1080" nom. (2.74 mm)

**2. INSULATION:**

- 2.1 Extruded PFA.
- 2.2 Wall thickness: .0394" nom. (1.00 mm)
- 2.3 O.D.: .1868" nom. (4.74 mm)
- 2.4 Color: natural.




**3. PERFORMANCE:**

- 3.1 Voltage rating: 25 KVDC
- 3.2 Temperature rating: 200°C

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done:				 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com						
								Date:	June 21, 2017									
								Verified:										
								Date:	June 21, 2017									
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								Size:	A	Scale:	---	Page:	1 of 1	Code Ident. No:	57104	Specification No.:	Q04266-X	Rev.: