



GENERAL PRODUCT SPECIFICATION
 Phone 800-316-8877 Fax 978-368-1275
 www.jamesmonroewire.com

Description: Four 20 AWG Insulated Conductors
 Overall Foil Shield, and PVC Jacket

Date: 7/26/2017

JM Part Number: JM57888

Reference: 32045976

Components Four 20 AWG Insulated Conductors

Conductor: 20 AWG, 71.0121 tinned copper

Insulation: .010" nominal wall of SR-PVC (see color code) .056"

Cable Construction

Cabling: Four insulated conductors cabled together - no fillers

Drain Wire: 20 AWG, 71.0121 tinned copper

Foil Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .040" nominal wall of Black Pressured PVC .220" ± .010"

Print (White Inkjet)

E66440 4/C 20 AWG SHIELDED 3/4 AWM 2517 105C 300V VW-1 ---
 LL41103 CSA AWM I/II A/B 105C 300V FT1 --- CE ROHS

Color Code

1. Black 2. Red 3. Green 4. White

Requirements

Temperature: -40°C to 105°C
 Voltage: 300V

Approvals: AWM Style 2517, VW-1
 CSA AWM, FT1
 Material are RoHS Compliant
 (2011/65/EU & EU 2015/863)

Written By:	rac	7/26/2017	Rev. 0	Initial Issue
Revised By:	scs	8/1/2017	Rev. 1	Added JM and Reference Numbers
Revised By:				
Revised By:				