



<b>Technical Data Sheet:</b>	<b>DS290/0813</b>
<b>Product Description</b>	<b>Standard weight uPVC corrugated pliable conduit</b>
<b>Product Range</b>	<b>FPL- Non-Metallic Conduits</b>

Roman Way, Coleshill  
Birmingham  
B46 1HG  
Tel: 00 44 (0)1675 466900  
Website: www.flexicon.uk.com



Above picture illustrates Conduit complete with FLK fitting



**Material;**  
u PVC

**Colour:**  
Black  
Grey (RAL 7045)  
White

**Fire Performance:**  
Self extinguishing to EN61368-1 (BSI Report No. 2381/7847798)

**IP Rating:**

- IP66 with FLK & FPA fittings

**Applications:**  
Buildings, particularly where buried in concrete or plaster.

Acid resistant

**Compression Strength:**  
150kg/100mm (20mm size)

**Pull-off (Tensile) strength :**  
25kg with FLK (20mm size)

**Temperature Performance:**  
-5°C to +70°C

Nominal Size	Part No	Dimensions and Mechanical Properties			
		Reel Length (M)	OD (mm)	ID (mm)	Min Bend radius R (mm)
16	<b>FPL16B-100M</b>	100	16	12	25
20	<b>FPL20B-100M</b>	100	20.0	15	30
25	<b>FPL25B-50M</b>	50	25.0	19.5	40
32	<b>FPL32B-25M</b>	25	34.5	27.9	50

**Compliance, Approvals & Accreditation;**



EN 61386 Classification Available on request

Russian Fire Safety Certificate No. 0642449

**Typical Applications;**



Errors, omissions and amendments excepted. As part of continuing product development Flexicon Ltd reserve the right to alter product specifications without prior notice. Data given is correct at time of compilation. Product specification and application data is for guidance only and does not constitute a warranty of any kind, either expressed or implied for Flexicon products or their suitability for a specific purpose. Third party approvals may be limited to certain sizes within a product range.