



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Conxall 316-P26R

Issue Date: 8/7/2017
Issue: 1

Construction

Description:	3/C 16 65/34 BC PVC/PVC STOOW	Diam. (In)
Component:	3 Conductors	
Conductor:	16 AWG 65/34 Bare Copper to ASTM B-174	0.059"
Insulation:	0.03" Premium Grade PVC	0.119"
Color Code:	Black, Green, White	0.119"
Cable Assembly:	3 Conductors Cabled	0.256"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.256"
Separator:	Clear Mylar or Tissue Separator	0.259"
Jacket:	0.075" Premium Grade UL PVC	0.409"
Jacket Color:	Black	0.409"
Print:	E322633 (UL) 16/3 STOOW 105°C 600V FT-2 --- c(UL) S TOOW 3/C 1.31 mm ² (16 AWG) 105°C 600V FT-2 --- Sun Res Outdoor Use	

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>		
UL	STOOW	105°C	600	FT-2		
Canadian cRU	AWM	80°C	300	FT-1	I/II	A/B

Environmental Compliance	
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2) • REACH Regulation 169: • California Prop 65: 	IQ170366