



Construction:

OD (In.)

1) Conductor:	26 AWG 7/.0067" Silver Plated Copper Coated Steel (SPCCS)	0.0201 +/- 0.001"
2) Dielectric:	Extruder PTFE	0.060 +/-0.003"
3) Inner Braid:	Round Silver Plated Copper 90% min. coverage	0.078" nom.
4) Outer Braid:	Round Silver Plated Copper 90% min. coverage	0.096" max.
5) Jacket:	Brown Tint FEP	0.114 +/- 0.004"
Surface Print:	"M17/152-00001 MIL-DTL-17 27478 HARBOUR INDUSTRIES"	

Physical Characteristics:

1) Weight per 1000 ft:	18.5 lbs. nom.
2) Minimum bend radius:	0.57"
3) Minimum continuous length:	50 ft
4) Operating temperature range:	-55C + 200 °C
5) RoHS compliance:	Complies with RoHS (Directive 2002/95/EC)

Electrical Characteristics:

Test Method:

1) Impedance:	50.0 +/- 2 ohms	1) Test Points	801
2) Capacitance:	32 pF/Ft max.	2) IF Band Width:	35 Khz
3) Velocity of Propagation:	69.5 % nom.	3) Sweep Time:	6 Sec
4) Time Delay:	1.5 ns Max.	4) Test Length:	10 ft
5) Attenuation:		5) Connector Type:	Male SMA plug
		6) Sampling Plan:	Per Mil-STD-105
	dB/100 ft		
	Freq. (GHz)		
	0.05		
	0.50		
	1.00		
	3.00		
	10.00		
	12.40		
	Max.		
	7.5		
	26.0		
	40.0		
	75.0		
	170.0		
	200.0		

Harbour Industries
 4744 Shelburne Rd., Shelburne, VT 05482
 PH: 802-985-3311 Fax: 802-985-0726 www.harbourind.com



Drawn By:	S. Wooster	This drawing contains proprietary information and is issued in strict confidence and shall not be copied, reproduced, transmitted or disclosed to any third party either wholly or in part without prior written approval of Harbour Industries . All copies outside of the Harbour Industries CAD system are Uncontrolled .					
Approved By:	M.T. Piner						
Date:	12/8/09	Part Number:	J2895	Rev:	C	Sheet:	1 of 1
Scale:	None					Drawing Number:	031896_3
Drawing Name:							
							M17/152-00001