



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 8/22/2017

Construction

Issue: 1

Description: 4/C 22 7/30 TC SR-PVC/PVC		Diam. (In)
Component:	4 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.03"
Insulation:	0.01" SR PVC	0.05"
Color Code:	Red, Blue, Green, Black	0.05"
Cable Assembly:	4 Conductors Cabled	0.121"
Separator:	Non-Woven Polyester	0.124"
Jacket:	0.038" PVC, Oil, Gas, Moisture and UV Resistant VW-1	0.2"
	Pressure Extruded For Roundness -- O.D.: .200" +/- .005"	
Jacket Color:	Black	0.2"
Print:	E174416 RU AWM-2464 80C 300V VW-1 - - - cRU AWM I/II AB 80C 300V FT-1	

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	
UL	AWM-2464	80°C	300	VW-1	
Canadian cRU	AWM	80°C	300	FT-1	I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170407

Jon Cunn
 8/22/17