

Aerospace Part#: TBD

CONTROL CABLE

DESCRIPTION

2 Conductors AWG 26/7x34 SPC
Unshielded FEP/FEP Black UL AWM Inner 1901 Style 20710 200C 600V

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
2	26/7x34	Silver Plated Copper	FEP	.016"	.051"

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Black	.015"	.132" Nom.	2" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -80C to 200C	10 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 600 Volts

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

UL AWM	1901, 20710
Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Flame Test	UL VW-1 - 1581 - 1202

MISCELLANEOUS

Markings: E157093 c RU us AWM STYLE 1901, 20710 600V 26 AWG (UL) 200C FEP/FEP

Color: Black / Red /
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com



LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS

* Specification subject to error and may change without notice