

STAINLESS STEEL BRAID

<u>CCC NO.</u>	<u>NOM. I.D. WHEN ROUNDED</u>	<u>AWG. OF INDIV ENDS</u>	<u>NO. OF STRANDS (CARRIER)</u>	<u>NO. OF WIRES PER STRAND</u>	<u>TOTAL NO. OF INDIV. WIRES</u>	<u>APPROX. SHIPPING WEIGHT</u>
302	1/32"	36	16	3	48	7
304	1/16"	36	24	2	48	7
306	5/64"	36	24	3	72	9
308	7/64"	36	24	4	96	11
310	1/8"	36	24	5	120	13
312	5/32"	34	32	6	192	30
314	11/64"	36	24	7	168	17
316	3/16"	36	24	8	192	19
318	7/32"	36	24	10	240	23
320	1/4"	36	24	13	312	28
322	1/4"	34	32	8	256	34
324	5/16"	32	32	8	256	36
326	3/8"	36	48	7	336	32
328	7/16"	36	48	8	384	39
330	1/2"	36	48	9	432	43
332	5/8"	36	48	11	528	50
334	3/4"	36	48	15	720	63
336	7/8"	36	48	18	864	78
338	1"	30	48	7	336	129

NOTES

1. These braids may be constructed with types 302, 304, 321, or 430 stainless steel. The differences are outlined on page 2 of this sheet.
2. These tubular braids can be flattened. Call us for your requirements.

Continental Cordage Corporation



INTERNATIONAL WIRE
Continental Cordage
 315-655-9800 phone
 315-655-9686 fax