HellermannTyton

Article Number: 151-28529

Description: Adhesive Base, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66/SR T50, White, 100/pkg



Base Data Local Order Number MB5A10C2 MB5A Type Color White (WH) Features and benefits • For use with 18 and 30 pound cable ties to provide stability when securing bundles. • Secures with rubber based adhesive backing and/or two or four screws. · 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles. Quantity Per bag **Product Description** Adhesive Fastened Mounting Bases are used with 18 through 150 lb. cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The four-way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles. Global Part Name MB5A-PA66-WH Short Description Adhesive Base, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66/SR T50, White, 100/pkg Product Dimensions Length L (Imperial) 1.49" Length L (Metric) 37.7mm **Fixation Method** Screw Mounting and Adhesive Width W (Imperial) 1.49" Width W (Metric) 37.7mm Cable Tie Width Max. (Imperial) 0.35" Cable Tie Width Max. (Metric) 8.9mm Height H (Imperial) .28" Height H (Metric) 7.10mm Mounting Hole Diameter D (Imperial) 0.19" Mounting Hole Diameter D (Metric) 4.8 mm Mounting Hole Centers (Imperial) 1.0"

151-28529

HellermannTyton

| Material | Polyamide 6.6 (PA66) |
|--------------------------------|---|
| Material Shortcut | PA66 |
| Adhesive | Synthetic rubber with base of polyethylene foam |
| Adhesive Operating Temperature | -4°F to +122°F (-20°C to +50°C) |
| Flammability | UL 94 V2 (excluding adhesive) |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| REACH Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Recognized (US and Canada) | Yes |
| | |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100Pieces |
| Customs Number(Schedule B) | 3926909987 |
| Content Unit (BMEcat) | pieces |
| Weight (Metric) | 1.8kg |
| | Material Shortcut Adhesive Adhesive Operating Temperature Flammability Operating Temperature REACH Compliant (Article 33) ROHS Compliant UL Recognized (US and Canada) UL Recognized (US and Canada) Package Quantity (Imperial) Package Quantity (Metric) Customs Number(Schedule B) Content Unit (BMEcat) |