



Rowe Industries | 626 Main St. | Ceredo, WV 25507 |
 Ph 302-855-0585, Fax 302-855-9182
www.roweindustries.com

STANDARD MANUFACTURING PROCEDURE

SMP#: SW168Q4D00
 CUSTOMER:
 ORDER-LINE-RELEASE NUMBER:
 COLOR: GRAY UL & CSA PRINTED

=====
 PART DESCRIPTION: #16 26/30 TC, WHT UL 3239 - 25KV/.062" WALL CSA TV-25
 =====

DIMENSIONS: #16 AWG - 26/30 TC NOMINAL OD: 0.058"
 STRAND DIAMETER: 0.010"
 CONDUCTOR WEIGHT: 8.3 Lbs/M'
 FINISHED WIRE OD: 0.186" +/- 0.004"
 MINIMUM AVERAGE WALL: 0.062"
 MINIMUM WALL AT ANY POINT: 0.056"

UL & CSA

RU AWM STYLE 3239 25KVDC 150C VW-1 E61355 CSA LL103756 TV-25 150C FT-1 16AWG
 CONFIRM PRINTWHEEL WITH FOREMAN OR SUPERVISOR

(*) SPARK VOLTAGE: 17.5 KVAC
 =====

=====
 =====

REVISION INFORMATION							
REV.	DESCRIPTION	ECO NUMBER	DATE	BY	ENGINEER	WIRE MAN.	VP OPS
H	UPDATED	ECN-9777	01-29-98	PFR	PFR	JAD	S.E.