

 RoHS HPC 3:1 Shrink Ratio MILITARY Specification Heatshrink Tubing Sleeves - SPOOL Format HIGH PERFORMANCE CONTINUOUS SEIP PRICE SHEET																	
NOMINAL MARKER SIZE	WHITE	YELLOW	OPERATING TEMP DEGREE	FULL RECOVER SHRINK TEMP	1 - 4 SPL PRICE PER METER	5 - 9 SPL PRICE PER METER	10+ SPL PRICE PER METER										
1/16	HPC 1/16 WE 30M SPL 3X	HPC 1/16 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	1.07	0.98	0.92										
3/32	HPC 3/32 WE 30M SPL 3X	HPC 3/32 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	1.07	0.98	0.92										
1/8	HPC 1/8 WE 30M SPL 3X	HPC 1/8 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	1.10	1.00	0.95										
3/16	HPC 3/16 WE 30M SPL 3X	HPC 3/16 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	1.25	1.14	1.07										
1/4	HPC 1/4 WE 30M SPL 3X	HPC 1/4 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	1.52	1.38	1.31										
3/8	HPC 3/8 WE 30M SPL 3X	HPC 3/8 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	2.03	1.85	1.75										
1/2	HPC 1/2 WE 30M SPL 3X	HPC 1/2 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	2.65	2.42	2.28										
3/4	HPC 3/4 WE 30M SPL 3X	HPC 3/4 YW 30M SPL 3X	-55c to +135c	plus 90 degree c	3.40	3.10	2.93										
1	HPC 1 WE 20M SPL 3X	HPC 1 YW 20M SPL 3X	-55c to +135c	plus 90 degree c	4.45	4.06	3.83										
1 1/2	HPC 1-1/2 WE 20M SPL 3X	HPC 1-1/2 YW 20M SPL 3X	-55c to +135c	plus 90 degree c	4.79	4.37	4.13										
<table border="0" style="width:100%"> <tr> <td style="width:15%">Product Type</td> <td style="width:35%">Length/Description</td> <td style="width:15%">Color</td> <td style="width:15%">Shrink Ratio</td> <td style="width:20%"></td> </tr> <tr> <td>HPC 3:1</td> <td>UOM = Meter</td> <td>WE = White YW = Yellow BK = Black</td> <td>3X = 3:1</td> <td>Standard Packaging = Spool Standard Colors = White, Yellow, Black, others by request Leadtime = Stock to 4 Weeks Terms: Net 30, FOB San Marcos, CA MOQ= \$500</td> </tr> </table>								Product Type	Length/Description	Color	Shrink Ratio		HPC 3:1	UOM = Meter	WE = White YW = Yellow BK = Black	3X = 3:1	Standard Packaging = Spool Standard Colors = White, Yellow, Black, others by request Leadtime = Stock to 4 Weeks Terms: Net 30, FOB San Marcos, CA MOQ= \$500
Product Type	Length/Description	Color	Shrink Ratio														
HPC 3:1	UOM = Meter	WE = White YW = Yellow BK = Black	3X = 3:1	Standard Packaging = Spool Standard Colors = White, Yellow, Black, others by request Leadtime = Stock to 4 Weeks Terms: Net 30, FOB San Marcos, CA MOQ= \$500													
Typical Features of HPC:																	
Meets Mil-Spec AMS-DTL 23053/5, Class 1, RoHS Compliant, (With exception to dimensions & longitudinal change).UL224, VW-1, Flame retarded, self-extinguishing																	
Continuous design allows for customized marking length requirement.																	
Markers supplied in spooled form, flattened continuous format on a carrier designed for use with Sumitag printers.				Effective 7/01/2016													