



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

C5811

Issue Date: 1/10/2018

Construction


IEWC: 32049409

Issue: 1

Description:	2/C 18 16/30 BC PE/PVC & OAS + DR	Diam. (In)
Component:	2 Conductors	
Conductor:	18 AWG 16/30 Bare Copper to ASTM B-174	0.048"
Insulation:	0.016" Polyethylene HDPE	0.08"
Color Code:	Black + White	0.08"
Cable Assembly:	2 Conductors Cabled	0.16"
Drain Wire:	20 10/30 Bare Copper Drain Wire In	0.16"
Shield:	Aluminum Mylar Foil Shield 25% Overlap Foil In	0.163"
Jacket:	0.025" PVC, Oil, Gas, Moisture and UV Resistant	0.215"
Jacket Color:	Blue	0.215"
Print:	WELDON TECHNOLOGIES V-MUX® P/N : OL20-1600-00 --- RU AWM 60C 300V E177416 --- cRU AWM I/II A/B 60C 300V FT1	

Specifications:	AWM Style	Temp	Voltage	Flame
UL	AWM-2092	60°C	300	FT-1
Canadian cRU	AWM	60°C	300	FT-1 I/II A/B

Environmental Compliance	
<ul style="list-style-type: none"> RoHS EU Directive 2011/65/EU (1&2) REACH Regulation 169: California Prop 65: 	IQ170481



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 1/10/2018
Issue: 1

Drawing/Rotation:

