



Domtech Inc.  
40 East Davis Street  
Trenton, Ontario  
Canada, K8V 6S4  
Ph: 613-394-4884  
Fax: 613-394-5372  
Toll Free: 888-278-8258 (USA & Canada)  
[www.domtech.net](http://www.domtech.net)

**FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT**

PRODUCT SPECIFICATION

October 16, 2017

PART NUMBER: 3822144

DESCRIPTION: AWM 22(7T)/4 80C 300V NO RIPCORD BLACK  
.191",CC150(BLK-LGRN-RED-WHT),PN662,CMG/AWM2464/2576/CM,FT4,UL/CSA  
BARREL PACK,3109M(10200FT)

CONDUCTOR: Stranded #22 awg 7x.0010" soft tinned copper

INSULATION: PVC .010" minimum average thickness, .052" +/- .002" diameter

ASSEMBLY: Cabled without fillers and a 4.000" +/- .125" lay  
Silicone separator, no ripcord

COLOUR SEQUENCE: Black-White-Red-Light Green

JACKET: PVC .030" minimum average thickness

DIAMETER: .191" +/- .010"

TEMPERATURE: AWM 80°C, CMG/CM 60°C

FLAME RATING: FT4

VOLTAGE RATING: 300V

PRINT TYPE: Ink jet

PRINT LEGEND: (UL) CM 22 AWG E132773 OR AWM 2576/2464 80C  
300V --- CSA CMG 22 AWG 60C FT4 LL39965

SPECIFICATIONS: CSA C22.2 No 214  
UL 758 - Style 2576, 2464  
UL 444  
RoHS Compliant

REGULATORY: CSA File #LL39965  
UL File #E76241  
UL File# E132773