

Article Number: 157-00205

Description: One Piece Cable Tie w/Oval Fir Tree, Mounting Hole Dia. 6.2-13.0mm, PA66HIRHS, Gray, 500/pkg

HellermannTyton 6.2-13.0mm, PA66HIRHS, Gray, 500/pk

| Base Data | | |
|-----------------------|---------------------------------|---|
| | | |
| | Local Order Number | 157-00205 |
| | Туре | T50ROSFTOVAL25A |
| | Color | Gray (GY) |
| | Features and benefits | The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole. The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. The oval hole fir tree fits 4 common automotive oval hole sizes. The specific connector slot on this part reduces rattle and movement of clip to the wire harness connector. |
| | Quantity Per | carton |
| | Product Description | The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. |
| | GLOBAL PART NAME | T50ROSFTOVAL25A-PA66HIRHS-GY |
| | Short Description | One Piece Cable Tie w/Oval Fir Tree, Mounting Hole Dia. 6.2-13.0mm, PA66HIRHS, Gray, 500/pkg |
| Product Dimensions | | |
| | Length L (Imperial) | 9.0" |
| | Fixation Method | Fir Tree for oval holes |
| | Identification Plate Position | none |
| | Offset Length (Metric) | 25.0mm |
| | Releasable Closure | No |
| | Tie Closure | plastic pawl |
| | Width W (Imperial) | 0.19" |
| | Width W (Metric) | 4.7mm |
| | Bundle Diameter Min. (Imperial) | 0.08" |
| | Bundle Diameter Min. (Metric) | 2.0mm |

generated on: 10/26/2017

157-00205



| Product Dimensions | Bundle Diameter Max. (Imperial) | 1.97" |
|-----------------------------|--|---|
| | Bundle Diameter Max. (Metric) | 50.0mm |
| | Panel Thickness Max. (Imperial) | 0.27" |
| | Panel Thickness Max. (Metric) | 6.75mm |
| | Panel Thickness Min. (Imperial) | 0.02" |
| | Panel Thickness Min. (Metric) | 0.60mm |
| | Mounting Hole Diameter D (Imperial) | 0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47" |
| | Mounting Hole Diameter D (Metric) | 6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm |
| | Mounting Hole Diameter D Min. (Imperial) | 0.24" |
| | Mounting Hole Diameter D Max. (Imperial) | 0.51" |
| Material and Specifications | | |
| | Material | Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) |
| | Material Shortcut | PA66HIRHS |
| | Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 500 |
| | Package Quantity (Metric) | 500 |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |

generated on: 10/26/2017