



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 bhanlon@huesonwire.com

Issue Date: 10/6/2017

Issue: 1

Construction

Description: 2/PR 20 10/30 TC PP/PUR & OAS + DR		Diam. (In)
Component:	2 Pairs	
Conductor:	20 AWG 10/30 Tinned Copper to ASTM B-174	0.036"
Insulation:	0.01" Polypropylene	0.056"
Color Code:	Supplied	0.056"
Cable Assembly:	2 Pairs Cabled	0.190"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.190"
Drain Wire:	20 10/30 TC	0.190"
Shield:	Aluminum/Mylar (foil In)	0.193"
Separator:	Tissue Paper	0.193"
Jacket:	0.05" Polyurethane	0.293"
Jacket Color:	Black 90°C 300 Volts	0.293"

Print:

Specifications: AWM Style Temp Voltage Flame
UL
 Canadian cRU

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170511



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/6/2017
Issue: 1

Drawing/Rotation:

IQ170511