



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/6/2017

Issue: 1

Construction

Description:	2/PR Ind Shld 18 16/30 TC PP/PUR	Diam. (In)
Component:	2 Pairs Individually Shielded	
Conductor:	18 AWG 16/30 Tinned Copper to ASTM B-174	0.047"
Insulation:	0.01" Polypropylene	0.067"
Color Code:	Supplied	0.067"
Cable Assembly:	2 Pairs Ind. Shielded with 18 16/30 TC Drains (Each Pair .138" Nom.)	0.276"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.276"
Separator:	Tissue Paper	0.276"
Jacket:	0.048" Polyurethane	0.372"
Jacket Color:	Black 90°C 300V	0.372"

Print:

Specifications: AWM Style Temp Voltage Flame

UL

Canadian cRU

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170514



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/6/2017
Issue: 1

Drawing/Rotation:

IQ170514