



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/6/2017

Issue: 1

Construction

Description: 6/C 16 26/30 TC PP/PUR & OAS + DR		Diam. (In)
Component:	6 Conductors	
Conductor:	16 AWG 26/30 Tinned Copper to ASTM B-174	0.066"
Insulation:	0.015" Polypropylene	0.096"
Color Code:	Supplied	0.096"
Cable Assembly:	6 Conductors Cabled	0.288"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.288"
Drain Wire:	18 16/30 TC	0.288"
Shield:	Aluminum/Mylar (foil In)	0.291"
Separator:	Tissue Paper	0.291"
Jacket:	0.045" Polyurethane	0.381"
Jacket Color:	Black 90°C 300 Volts	0.381"

Print:

Specifications: AWM Style Temp Voltage Flame

UL

Canadian cRU

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170515



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/6/2017
Issue: 1

Drawing/Rotation:

IQ170515