



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/20/2017

Issue: 1

Construction

Description: 4/C 20 7/28 TC PVC/PVC		Diam. (In)
Component:	4 Conductors	
Conductor:	20 AWG 7/28 Tinned Copper to ASTM B-8	0.038"
Insulation:	0.013" Premium Grade PVC	0.064"
Color Code:	Blue, White, Black, Red	0.064"
Cable Assembly:	4 Conductors Cabled	0.155"
Separator:	Optional	0.158"
Jacket:	0.032" PVC CMG FT-4	0.222"
Jacket Color:	Chrome Gray	0.222"

Print: E194074 20 AWG (UL) TYPE CM 75C OR AWM 2464 80C 300V --- C(UL) TYPE CMG 75C FT-4 --- ROHS

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	
UL	AWM-2464	80°C	300	VW-1	
Canadian cRU	AWM	80°C	300	FT-1	I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170524