

# Type W - Multi Conductor

## Construction Parameters:

**CONDUCTOR:** 4 AWG stranded bare copper  
**INSULATION:** EPDM  
**COLOR CODE:** 5/C: Gray, Black, Brown, Blue, Green/Yellow  
**CORE BINDER:** Tape with Nylon Braid (80% Coverage)  
**JACKET:** CPE  
**COLOR:** Black  
**INDENT LEGEND:** 4 AWG 5/C TYPE W PORTABLE POWER CABLE 90C - WET OR DRY 2000V OIL AND SUN. RES. (UL) P-136-35-MSHA --- AIW(TM) E172226 --- C(UL) FT1/FT5 -40C

## PHYSICAL PROPERTIES:

**TEMPERATURE RANGE:** -40°C to 90°C  
**OIL RESISTANT:** Yes  
**WATER RESISTANT:** Yes

## ELECTRICAL PROPERTIES:

**VOLTAGE RATING:** 2000V rms, Max

## Industry Approvals:

- o UL Subject 1650
- o NEC Article 400
- o CSA C22.2 No. 96
- o Passes CSA FT1, FT5 Horizontal Flame Tests
- o MSHA

Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	
				Inches	mm	Inches	mm	Lb./kft.	kg/km	NEC	CEC
672330	4	5	259 Str	0.060	1.52	1.400	35.56	1350	2009	91	97

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

\* Ampacity based on NEC Table 400.5(B) and CEC Table 12A.

This product complies with European Directive (EU) 2015/863 – RoHS 3

The customer will accept all factory lengths and +/- 10 percent of total order requested.

Customer Name: \_\_\_\_\_ Date Signed: \_\_\_\_\_

Customer Approval: \_\_\_\_\_

Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | [www.southwire.com](http://www.southwire.com)

Copyright © 2019 Southwire Company, LLC. All Rights Reserved



Specification Issue Date: March 4, 2020