



Specification Sheet

Lake Cable Part #: S284TPUR-NUL

Description: 28 AWG 4 conductor 7 strand tinned copper wire, XLPE insulation, shielded, and an overall pressure extruded PUR jacket.

- 1. **Conductor**
 - 1.1. AWG Size & Stranding: 28 AWG 7 Strands
 - 1.2. Material: Annealed Tinned Copper
 - 1.3. Conductor Count: 4 Conductors
- 2. **Insulation**
 - 2.1. Material: Cross-Linked Polyethylene
 - 2.2. Wall Thickness: 0.007"
 - 2.3. Color Code: Black, White, Red, Green
- 3. **Assembly**
 - 3.1. Nominal Lay Length: 1.25" LHL (9.6 tw/ft)
 - 3.2. Binder: Clear Mylar Wrap - 100% Coverage
 - 3.3. Braid Shield: 80% Minimum Coverage - Tinned Copper
- 4. **Jacket**
 - 4.1. Material: Pressure Extruded Polyurethane
 - 4.2. Convolution Level: 2 or Better
 - 4.3. Wall thickness: 0.020"
 - 4.4. Diameter: 0.125" ± 0.005"
 - 4.5. Color: Black
 - 4.6. Ripcord: No
 - 4.7. Weight: 12 Lbs/Mft
- 5. **Markings**
 - 5.1. Type: No
 - 5.2. Legend: No
 - 5.3. Footage Markers: No
- 6. **Standards**
 - 6.1. All materials used in the manufacture of this cable are RoHS II compliant
 - 6.2. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Mike Bernin 10/23/17

Signature
ACI

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION