

166-90190

HellermannTyton

Article Number: 166-90190

Description: HelaGuard Non-Metallic Conduit, Std. Weight, 0.38" Dia, Nylon PA6, Black, 100 ft/reel



Base Data	
Local Order Number	166-90190
Type	HG-SW0380
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Material is easy to use and cut; reduces installation time and labor costs. • Flexible, abrasion resistant and durable for a variety of applications. • Good impact strength; recovers quickly if crushed. • UV resistant; suitable for use in outdoor applications. • Offered in fine or course corrugated pitch.
Quantity Per	reel
Product Description	A standard weight corrugated conduit made of PA6 nylon that offers flexible abrasion protection for wire and cable bundles. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard non-metallic fittings for IP66 rating or greater protection against water, wind and dirt.
GLOBAL PART NAME	HG-SW0380-PA6-BK
Short Description	HelaGuard Non-Metallic Conduit, Std. Weight, 0.38" Dia, Nylon PA6, Black, 100 ft/reel
Product Dimensions	
Length L (Imperial)	100.0ft
Length L (Metric)	30.5m
Inner Diameter D (Imperial)	0.47"
Inner Diameter ID (metric)	11.8mm
Euro (NW) Size	12mm
Pitch Type	F (Fine)
Trade Size	3/8 "
Outside Diameter D (imperial)	0.63"
Outside Diameter OD (metric)	15.8mm
Nominal Diameter (Imperial)	3/8"
Nominal Diameter (Metric)	16mm
Inside Bend Radius (Imperial)	1.38"

166-90190



Product Dimensions	Inside Bend Radius (Metric)	35mm
Material and Specifications	Material	Polyamide 6 (PA6)
	Material Shortcut	PA6
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +248°F (-40°C to +120°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
	UL Recognized (US and Canada)	Yes
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		30.5m
Customs Number(Schedule B)		3926909987