



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/23/2017

Issue: 2

Construction

Description: 6/C 22 26/36 TC SR-PVC/PUR		Diam. (In)
Component:	6 Conductors	
Conductor:	22 AWG 26/36 Tinned Copper to ASTM B-174	0.030"
Insulation:	0.01" SR PVC	0.050"
Color Code:	Brown, Green, Yellow, Gray, Pink, Blue	0.050"
Assembly:	6 Conductors Cabled	0.150"
Fillers	No Filler	0.150"
Separator:	Non-Woven Separator Tape	0.153"
Jacket:	0.027" Polyurethane Jacket 0.210" +/- .010"	0.210"
Jacket Color:	Black	0.210"

Print: No Print Required

Specifications:	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
	90°C	300	FT-2
Issue 2: 8/7/2017	Changed Temp to 90°C Defined Cable Tolerance		

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ170336



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/23/2017
Issue: 2

Drawing/Rotation:

