



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 bhanlon@huesonwire.com

IEWC P/N 32050957

Issue Date: 6/18/2018

Construction

Hueson Wire C5365

Issue: 1

Description: 4/C 22 7/30 TC mPPE/mPPE		Diam. (In)
Component:	4 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.03"
Insulation:	0.01" mPPE UL Approved	0.05"
Color Code:	Black, Red, White, Green	0.05"
Cable Assembly:	4 Conductors Cabled	0.121"
Drain Wire:	22 7/30 TC Drain Wire In	0.121"
Filler:	Fibrulated Polypropylene Fillers for Roundness	0.121"
Shield:	Aluminum Mylar Tape (Foil Side In)	0.124"
Jacket:	0.035" mPPE Polyphyneylene	0.198"
Jacket Color:	Gray	0.198"
Print:	E174416 4C 22 AWG RU AWM 21819 105C 600V OR 21492 80C 300V VW-1 CLASS K C(RU) AWM I/II A/B FT1 600V 105C CE ROHS	

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM-21819	105°C	600	VW-1
	AWM-21492	80°C	300	
Canadian cRU	AWM	80°C	300	FT-1 I/II A/B

Environmental Compliance	
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2) • REACH Regulation 169: • California Prop 65: 	IQ180288



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 6/18/2018
Issue: 1

Drawing/Rotation:

