



192-10040 Article Number:

Snapper Hose Clamp, .41"-.46" Bundle Diameter, PA66GF13, Black, 100/pkg Description:

Base Data		
	Local Order Number	SNP4GHS0C2
	Туре	SNP4
	Color	Black (BK)
	Features and benefits	 Designed for quick, ratcheted installation and can be released and reused. Heat stabilized material is suitable for high temperature applications.
	Quantity Per	bag
	Product Description	Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.
	GLOBAL PART NAME	SNP4-PA66GF13-BK
	Short Description	Snapper Hose Clamp, .41"46" Bundle Diameter, PA66GF13, Black, 100/pkg
Product Dimensions		
	Fixation Method	Plug-in mounting
	Variant	Closed
	Width W2 (Imperial)	0.234"
	Width W2 (Metric)	5.94mm
	Bundle Diameter Min. (Imperial)	0.39"
	Bundle Diameter Min. (Metric)	10.4mm
	Bundle Diameter Max. (Imperial)	0.46"
	Bundle Diameter Max. (Metric)	11.7mm

generated on: 11/6/2017

192-10040



Product Dimensions	Diameter Min. (Imperial)	0.41"
	<u> </u>	
	Diameter Min. (Metric)	10.41mm
	Diameter Max. (Imperial)	0.458"
	Diameter Max. (Metric)	11.63mm
	Nominal Diameter (Imperial)	7/16"
	Nominal Diameter (Metric)	11mm
	Wall Thickness WT (Imperial)	.067"
	Wall Thickness WT (Metric)	1.7mm
Material and Specifications		
	Material	Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)
	Material Shortcut	PA66GF13
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	UV-Resistant (Yes/No)	No
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	0.18kg

generated on: 11/6/2017