

Description: Thirteen Conductor, 24 AWG
 Overall Foil Shield and PVC Jacket

Date: 11/14/2017

JM Part Number: TBD
Reference: BZ97

Components Thirteen 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .010" nominal wall of Semi-Rigid PVC (see color code) .044"

Cable Construction

Cabling: Thirteen conductors cabled together with FRPP Fillers

Drain Wire: 24 AWG, 7/32 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side In

Jacket: .032" nominal wall of Gray PVC (86 Shore A) .262"

Color Code

- | | |
|-----------|---------------|
| 1. Yellow | 8. Violet |
| 2. Orange | 9. White |
| 3. Black | 10. Gray |
| 4. Red | 11. Pink |
| 5. Brown | 12. Green |
| 6. Blue | 13. Red/Green |
| 7. Tan | |

Print (Black Inkjet)

E66440 13/C 24 AWG SHIELDED 9\ AWM 2464 80C 300V VW-1
--- CE ROHS

Requirements

Temperature: 80°C
 Voltage: 300V

Approvals: UL AWM Style 2464
 CE-LVD and RoHS Compliant
 (2011/65/EU & EU 2015/863)

Written By:	rac	11/14/17	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				