

ALPHA WIRE

Part Number: 17-2381

Issue:

Page 1 of 1 Pages

Issue Date:

10/30/2017

Cable Specification

Component 1 2 COND
Conductor: 16 (65/34) AWG TC
Insulation: 0.012" Wall, Nom. MPPE1
Color Code: 2 SOLID COLORS/ 1 STRIPED/ 1 NUMBER CODED

Final Assembly 2 Components
Core Wrap: NWP Tape, 25% Overlap, Min.
Jacket: 0.032" Wall, Nom., PUZH
Jacket OD: 0.228"
Jacket Color: BLACK

Approvals

UL: AWM/STYLE 21959
 60C OIL
 SUNRES
CSA: c(RU) AWM I/II A/B
 FT2
MIL: NONE
CE Compliant: YES
ROHS Compliant: YES
REACH Compliant: YES

Miscellaneous

Temperature: 90 C
Voltage: 600 V_{RMS}
Put Ups: 1000 FT PUTUP
Requested Quantity: 13000Ft.

Application Notes

Note:

Cable OD tolerance: +/-0.006".

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.