



Specification Sheet

Lake Cable Part #: P162F-02/03

Description: 16 AWG 2 conductor solid bare copper wire with plenum rated PVC insulation, unshielded and overall plenum rated PVC jacket for low-voltage electronic cable applications

- 1. Conductor**
 - 1.1.AWG Size & Stranding: 16 AWG Solid
 - 1.2.Material: Annealed Bare Copper
 - 1.3.Conductor Count: 2 Conductors
- 2. Insulation**
 - 2.1.Material: Plenum Rated Polyvinylchloride
 - 2.2.Wall Thickness: 0.009"
 - 2.3.Color Code: Black, Red
- 3. Assembly**
 - 3.1.Nominal Lay Length: 3.00" LHL (4.00 Tw/Ft)
 - 3.2.Shield: N/A
 - 3.3.Drain Wire: N/A
- 4. Jacket**
 - 4.1.Material: Plenum Rated Polyvinylchloride
 - 4.2.Wall Thickness: 0.015"
 - 4.3.Diameter: 0.170"
 - 4.4.Color: Red/Orange
 - 4.5.Ripcord: Yes
 - 4.6.Weight: 26 Lbs/Mft
- 5. Markings**
 - 5.1.Type: Cable permanently identified via surface inkjet print
 - 5.2.Legend: LAKE CABLE E171203 16AWG 2C (UL) FPLP OR (UL) CMP C(UL)US 75°C FT-6
"ROHS II" REACH MADE IN USA
 - 5.3.Footage Markers: Yes
- 6. Standards**
 - 6.1.Cable suitable for installation under NEC (NFPA 70) article 800 and article 760 for guidelines
 - 6.2.UL listed as type CL3P per UL standard 13 and as type FPLP 75°C per UL standard 1424
 - 6.3.All materials used in the manufacture of this cable are RoHS II and REACH compliant
 - 6.4.Maximum Operating Voltage: 300V
 - 6.5.Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of you order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION