



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

American Mustang® 600V SOOW

Construction Parameters:

CONDUCTOR: 18 AWG - 10 AWG Class K stranded bare copper per ASTM B-174
INSULATION: EPDM
JACKET: CPE
COLOR: Yellow (Other colors available upon request)
PRINT LEGEND: SOUTHWIRE® American Mustang® CORD X/C XX AWG (X.XXmm2) SOOW E46194 (UL) 600V -40C TO 105C -- CSA LL39753 SOOW 600V -40C TO 105C FT2 WATER RESISTANT

IDENT LEGEND: P-07-KA070018-1-MSHA

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -40°C to 105°C
WATER RESISTANT: Yes

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 600V rms, Max

Industry Approvals:

- o UL Standard 62
- o CSA Standard C22.2 No. 49
- o NEC Article 501.140 Class I Div. 2
- o NEC Article 400
- o Federal Spec JC580
- o Passes CSA FT2 Flame Test
- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Nom. DCR Ω/1M'	Color Code
				Inches	mm	Inches	mm	Lb./kft.	kg/km			
822245	18	2	16/30	0.030	0.76	0.346	8.79	65	97	10	6.59	Black, White
822345	18	3	16/30	0.030	0.76	0.365	9.27	84	125	10	6.59	Black, White, Green
822445	18	4	16/30	0.030	0.76	0.390	9.91	98	146	7	6.59	Black, White, Red, Green
822246	16	2	26/30	0.030	0.76	0.370	9.40	81	121	13	4.05	Black, White
822346	16	3	26/30	0.030	0.76	0.390	9.91	94	140	13	4.05	Black, White, Green
822446	16	4	26/30	0.030	0.76	0.415	10.54	118	176	10	4.05	Black, White, Red, Green
822247	14	2	41/30	0.045	1.14	0.500	12.70	134	199	18	2.55	Black, White
822347	14	3	41/30	0.045	1.14	0.525	13.34	169	251	18	2.55	Black, White, Green
822447	14	4	41/30	0.045	1.14	0.570	14.48	201	299	15	2.55	Black, White, Red, Green
822248	12	2	65/30	0.045	1.14	0.570	14.48	184	274	25	1.61	Black, White
822348	12	3	65/30	0.045	1.14	0.595	15.11	224	333	25	1.61	Black, White, Green
822448	12	4	65/30	0.045	1.14	0.645	16.38	276	411	20	1.61	Black, White, Red, Green
822249	10	2	104/30	0.045	1.14	0.615	15.62	225	335	30	0.98	Black, White
822349	10	3	104/30	0.045	1.14	0.660	16.76	299	445	30	0.98	Black, White, Green
822449	10	4	104/30	0.045	1.14	0.710	18.03	360	536	25	0.98	Black, White, Red, Green

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

* Ampacity based on NEC Table 400.5(A) and CEC Table 12.

This product complies with European Directive 2011/65/EU (RoHS-2)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: June 24, 2014