

ALPHA WIRE

Part Number: 17-1965

Issue:

Page 1 of 1 Pages

Issue Date:

8/10/2017

Cable Specification

Component 1 3 COND
Conductor: 22 (19/34) AWG TC
Insulation: 0.010" Wall, Nom. PVC/ 0.003" Wall NYLON
Color Code: ALPHA WIRE COLOR CODE G

Final Assembly 3 Components
Core Wrap: CM Tape, 25% Overlap, Min.
Shield: TC BRAID Shield, 90% Coverage, Min.
Drain Wire: 22 (19/34) AWG TC
Jacket: 0.017" Wall, Nom., PVC
Jacket OD: 0.184"
Jacket Color: SLATE

Approvals

UL: NONE
CSA: NONE
MIL: MIL-W-16878/Type B/N
CE Compliant: YES
ROHS Compliant: YES
REACH Compliant: NO

Miscellaneous

Temperature: 105 C
Voltage: 600 V_{RMS}
Put Ups: 1000 FT PUTUP
Requested Quantity: 1000Ft., 2500Ft., 5000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.