Date



Specification Sheet

Lake Cable Part #: C203CST-18

Description: 20 AWG 3 conductor 7 strand tinned copper wire, SRPVC insulation, shielded with an overall

PVC jacket. (UL) CMG or AWM 2464.

1. Conductor

1.1. AWG Size & Stranding: 20 AWG 7 Strands Class B 1.2. Material: Annealed Tinned Copper

1.3. Conductor Count: 3 Conductors

2. Insulation

2.1. Material: Semi-Rigid Polyvinylchloride

2.2. Wall Thickness: 0.015"

2.3. Diameter: 0.065" ± 0.002" 2.4. Color Code: Black, Red, White

3. Assembly

3.1. Nominal Lay Length: 2.00" LHL (6.00 Tw/Ft)

3.2. Shield: Aluminum/Mylar- 100% Coverage 3.3. Drain Wire: 22 AWG 7 Strands Tinned Copper

4. Jacket

4.1. Material: Polyvinylchloride

4.2. Wall thickness: 0.032"

4.3. Diameter: 0.206" ± 0.016"

4.4. Color: Gray
4.5. Ripcord: N/A
4.6. Weight: 28 Lbs/Mft

5. Markings

5.1. Type: Cable shall be permanently identified via surface inkjet print

5.2. Legend: LAKE CABLE E171197 20AWG 3C SHIELDED 75C C(UL)US CMG SUN RES FT4 OR

AWM 2464 300V 80C "ROHS COMPLIANT" MADE IN USA

5.3. Footage Markers: Yes

6. Electricals

6.1. Impedance: $66 \Omega \pm 10\%$ 6.2. Capacitance: $25 \text{ pF/ft.} \pm 10\%$ 6.3. DC Resistance: $10.7 \Omega/\text{Mft.} @ 20^{\circ}\text{C}$

7. Standards

- 7.1. Cable suitable for installation under NEC (NFPA 70) article 800 guidelines
- 7.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 7.3. C(UL)US listed as CMG per UL standard 444 and per CSA C22.2 No. 214-17
- 7.4. UL recognized component as AWM 2464, 80°C, 300V per UL standard 758
- 7.5. For internal wiring or external interconnection of electronic equipment
- 7.6. Cable meets (UL) 1685 FT4 flame test
- 7.7. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive
- 7.8. Cable is REACH compliant per Regulation (EC) No 1907/2006 (197) Updated January 15, 2019
- 7.9. Made in the USA
- 7.10. MARNING: This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION

you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature	
Company	•