



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 4/6/2018

Issue: 1

Construction

Description:	3/C 22 7/30TC SR-PVC/ PVC	Diam. (In)
Component:	3 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.03"
Insulation:	0.01" SR PVC	0.05"
Color Code:	Black + White + Violet	0.05"
Cable Assembly:	3 Conductors Cabled	0.108"
Separator:	Clear Mylar Tape 25% Overlap	0.108"
Jacket:	0.032" AWM Jacket Compound	0.172"
Jacket Color:	Gray	0.172"
Print:	E174416 RU AWM-2464 80C 300V and AWM-2576 80C 150V VW-1 - - - cRU AWM I/II AB 80C 300V FT-1	

Specifications:	AWM Style	Temp	Voltage	Flame
UL	AWM-2464	80°C	300	VW-1
	AWM-2576	80°C	150	
Canadian cRU	AWM	80°C	300	FT-1 I/II A/B

Environmental Compliance	
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2) • REACH Regulation 169: • California Prop 65: 	IQ180073