

Y65539 1212747E DESIGN B (LINE 4)  
 9744 EXCEPT COLOR CODE AND FILLERS

-CABLE-

ITEM NO: NEWy \_\_\_\_\_  
 DESC: \_\_\_\_\_  
 DATE: \_\_/\_\_/\_\_ REV: 0 PENG: DOB SENG: \_\_\_\_\_

CABLING:

PLANETARY (Y/N): N  
 LAY LENGTH & DIR: 2.25" L.H.  
 MARKER THREAD (Y/N): N  
 LAY-UP: 2 PR + 2 F \_\_\_\_\_  
 CW ROTATION: WHT & BLK/WHT PR, FILLER, BLK & RED PR,  
 FILLER  
 INNER TO OUTER TAPE TYPE DWG#: N/A  
 TAPE1-PULL-ON(Y/N): N SPIRAL(Y/N): N  
 DIR: \_\_\_\_\_ MIN LAP: \_\_\_\_\_  
 TAPE2-PULL-ON(Y/N): N SPIRAL(Y/N): N  
 DIR: \_\_\_\_\_ MIN LAP: \_\_\_\_\_  
 TAPE3-PULL-ON(Y/N): N SPIRAL(Y/N): N  
 DIR: \_\_\_\_\_ MIN LAP: \_\_\_\_\_  
 BINDER (Y/N): N # BINDERS: \_\_\_\_  
 SPACING: \_\_\_\_\_" LAY DIR: \_\_\_\_  
 CABLING DIA: .169" MAX CABLING DIA: .174"  
 SWEEP TEST CODE (Y/N): \_\_\_\_  
 BRAID SPIKE NOM FREQ (MHZ): \_\_\_\_\_  
 RECOMMENDED TEST CONE: \_\_\_\_\_

TESTING:

IN-PROCESS TESTING (Y/N): N  
 REQUIREMENTS:  
 INFO ONLY (Y/N): \_\_\_\_  
 SAMPLE LENGTH: \_\_\_\_\_  
 TESTING PARAMETERS: \_\_\_\_\_  
 FINISHED OPERATION TESTING (Y/N): N  
 REQUIREMENTS:  
 INFO ONLY (Y/N): \_\_\_\_  
 SAMPLE LENGTH: \_\_\_\_\_  
 TESTING PARAMETERS:  
 OTHER: CABLE TO BE SMOOTH AND ROUND \_\_\_\_\_  
 REFERENCE NUMBER: \_\_\_\_\_

P.O.M.	30	OTHER:	
DATE:		INITIALS:	

BILL OF MATERIALS

Component	Fac	Description	U/M	Qty Required
-----	---	-----	---	-----
7674Y A3N	30	TW PR WHT & BLK/WHT	FT	
7674Y 061	30	TW PR #22 PVC BLK & RED	FT	
T3113 009 (2x)	30	.090 PP FILLER	LB	

ITEM #:	
ITEM DESCRIPTION:	
EXTRA DESCRIPTION:	

Brand	
Item Type	
Item Class	
Item Status	
Stocking U/M	
Lot Cont	
Code	
Color	
Size	
Size UOM	
Size 2	
Size 2 UOM	
UPC	
Purch U/M	
Selling U/M	
Conv	
Pricing U/M	
Allocation	
Cust Min Order Qty	
Cust Std Order Qty	
COO/Drop Ship Allowed	
Harm Code	
Tariff Class	

Annex	
Copper Wgt	
Cpr wgt Manual/Enable Cpr Price	
Group Tech 2	
Stand Batch Size	
Max Tol %	
Tol	
Package Size	
NPD Date (YYMM)	
Units Per Pallet	
Net Net Wgt	
Length	
Width	
Height	
U/M	
Weight	
U/M	
Celsius (ROHS)	
Fahrenheit (Sp Gr)	
DRP100	
To	
From	
Canada Item Master Entered	

- JACKET -

ITEM NO: Y65539 060 \_\_\_\_\_

DESC: \_\_\_\_\_

DATE: \_\_/\_\_/\_\_ REV: \_0\_ PENG: DOB \_\_\_\_\_ SENG: \_\_\_\_\_

UL: E108998, VOL. 5, SEC. 20, PG. 1; E-12683, PG. 2576

JACKET:

CUSTOMER DRAWING (Y/N): N

TAPE APPLIED AT JACKETING (Y/N): N

LATERAL/CORRUGATED: \_\_\_\_\_

SPIRAL DRAIN (Y/N): N

LAY: \_\_\_\_\_ QTY: \_\_\_\_\_

JACKET PROFILE TYPE #: 17 \_\_\_\_\_

WALL TYPE: SEMI-TUBE

NOM WALL: .032" MIN AVG: .030" (UL)

ABS MIN: .024" (UL)

MAX AVG: \_\_\_\_\_

ABS MAX: \_\_\_\_\_

JKT DIA: .233" +/- .006" \_\_\_\_\_ MIN DIA: \_\_\_\_\_

MAX DIA: \_\_\_\_\_

MIN. CONCENTRICITY: \_\_\_\_\_

MESSENGER (Y/N): N

MARKER THREAD (Y/N): N

PRINT TYPE: INK \_\_\_\_\_ OFFSET \_\_\_\_\_

INKJET XX INDENT \_\_\_\_\_

CUSTOMER REQ'D INK COLOR: \_\_\_\_\_  
 MARKER TAPE (Y/N):  N  WIDTH: \_\_\_\_\_"  
 LEGEND: "BELDEN Y65539 CMG 2PR22 (UL) E108998 OR  
 AWM 2576 OR C(UL) CMG"  
 STRIPE TYPE: \_\_\_\_\_  
 COLOR(S): \_\_\_\_\_ WHEEL(S): \_\_\_\_\_  
 SPARK VOLTAGE: N/A  
 MAX.TEMP.RATING: 80C \_\_\_\_\_  
 MAX.VOLTAGE RATING: 300V \_\_\_\_\_

TESTING:  
 IN-PROCESS TESTING (Y/N):  N   
 REQUIREMENTS:  
 INFO ONLY (Y/N):  N   
 SAMPLE LENGTH: \_\_\_\_\_  
 TESTING PARAMETERS: \_\_\_\_\_

FINISHED OPERATION TESTING (Y/N):  Y   
 REQUIREMENTS:  
 INFO ONLY (Y/N):    
 SAMPLE LENGTH: \_\_\_\_\_  
 TESTING PARAMETERS: \_\_\_\_\_

DIELECTRIC WITHSTAND PER DIVISION QA TEST  
 PROCEDURE 6001 (LATEST REVISION) UL/E108998  
 OTHER: JACKET SHALL NOT BOND TO SINGLES. CABLE TO BE  
 SMOOTH AND ROUND.

RoHS COMPLIANT (Y/N):  Y   
 REFERENCE NUMBER: 9744 EXCEPT CC AND FILLERS  
 HARMONIZATION CODE: \_\_\_\_\_  
 COPPER WEIGHT MANUAL (M): N/A  
 COPPER WEIGHT:  .  LBS / FT  
 ENABLE COPPER PRICING (Y/N):  N

NEW ITEM CLASSIFICATION: KF\_

P.O.M.	30	OTHER:	
DATE:		INITIALS:	

BILL OF MATERIALS

Component	Fac	Description	U/M	Qty Required
-----	---	-----	---	-----
T950	30	SILICONE CABLE LUBR	GL	
INKJETN 006	30	NOGALES BLUE INKJET	EA	
X46519	30	060 CHR (STD#3) FRP	LB	
NEWy	30	2 PR #22 PVC	FT	

ITEM #:	
ITEM DESCRIPTION:	
EXTRA DESCRIPTION:	

(RED TEXT=DEFAULT)

Brand	
Item Type (F)	
Item Class	
Item Status	
Stocking U/M (FT)	

Annex	
Copper Wgt	
Cpr wgt Manual/Enable Cpr Price	
Group Tech 2	
Stand Batch Size(1000)	

Lot Cont	
Code	
Color	
Size	
Size UOM (FT)	
Size 2	
Size 2 UOM (MT)	
UPC	
Purch U/M(FT)	
Selling U/M(FT)	
Conv	
Pricing U/M(FT)	
Allocation	
Cust Min Order Qty(5000)	
Cust Std Order Qty(5000)	
COO/Drop Ship Allowed	
Harm Code	
Tariff Class (8544.49.3080)	

Max Tol %	
Tol	
Package Size(1)	
NPD Date (YYMM)	
Units Per Pallet	
Net Net Wgt	
Length	
Width	
Height	
U/M (IN)	
Weight	
U/M	
Celsius (ROHS) (2)	
Fahrenheit (Sp Gr)	
DRP100	
To	
From	
Canada Item Master Entered	

-PUT-UP-

ITEM NO: \_\_\_\_\_  
DESC: \_\_\_\_\_  
DATE: \_\_/\_\_/\_\_ REV: \_\_ PENG: \_\_\_\_\_ SENG: \_\_\_\_\_

PUT-UP:  
SPARK VOLTAGE: N/A \_\_\_\_\_  
STRIPE TYPE: \_\_\_\_\_ TOP COTE (Y/N): \_\_\_\_  
STRIPE COLOR: \_\_\_\_\_  
WHEEL(S) : \_\_\_\_\_  
LENGTH REQUIREMENTS: \_\_\_\_\_  
\_\_\_\_\_  
SPECIAL MARKING AND/OR HANDLING: \_\_\_\_\_  
\_\_\_\_\_  
SPECIAL TESTING (Y/N) : N\_  
REQUIREMENTS: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

LABEL REQUIREMENTS:  
NO BELDEN I.D. ON LABELS (Y/N) : \_\_\_\_  
SPECIAL LABEL FORMAT(S) REQUIRED (Y/N) : \_\_\_\_  
IN PLACE OF REGULAR PRODUCT LABEL (Y/N) : \_\_\_\_  
\_\_\_\_\_  
IN ADDITION TO REGULAR PRODUCT LABEL (Y/N) : \_\_\_\_  
\_\_\_\_\_

OTHER: \_\_\_\_\_

-

CUSTOMER

-----

-

CUSTOMER PART #

-----

-

REFERENCE NUMBER: \_\_\_\_\_

HARMONIZATION CODE:

LIST ALL APPLICABLE PATENTS FOR PRINTING ON LABELS:

