



**Part Number: 35608**

Hook-Up/Lead Wire UL AWM Style 3195 - XL-DUR®, (1) 8 AWG (133x29)  
TC, XLPE, 600V, 125°C

## Product Description

One 8 AWG stranded (133x29) tinned copper conductor, cross-linked polyethylene insulation.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
8	133x29	TC - Tinned Copper	1

Conductor Count:	1
AWG Size:	8

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
XLPE - Cross Linked Polyethylene	0.263 in	0.048 in
XLPE - Cross Linked Polyethylene		

### Construction and Dimensions

#### Stranding

Lay Length
AWM 3195 mm

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
0.61 Ohm/1000ft

#### Voltage

UL Voltage Rating
600 V

### Temperature Range

UL Temp Rating:	125°C
-----------------	-------

### Mechanical Characteristics

Bulk Cable Weight:	74 lbs/1000ft
--------------------	---------------

### Standards

UL AWM Style:	3195
CSA Type:	CL1251
Military Specification:	N/A

### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2009-09-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Part Number

Plenum (Y/N):	No
---------------	----

## Variants

Item #	Color	Footnote
35608 0102000	BLACK	C F
35608 0092000	WHITE	C F

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.