

PROVO PART NUMBER  
**5709**

**MULTI-CONDUCTOR • FOIL + BRAID SHIELD • STRANDED TINNED  
COPPER CONDUCTORS • CONDUCTORS TWISTED • SR PVC  
INSULATION • 100% ALUMINUM FOIL SHIELD • 85% BRAIDED TINNED  
COPPER SHIELD • STRANDED TINNED COPPER DRAIN WIRE • PVC  
JACKET • -20°C +105°C**



SPEC CRITERIA	SPECIFICATION		
AWG	22		
STRANDING	7 x 30		
NUMBER OF CONDUCTORS	9		
DRAIN WIRE AWG	24		
INSULATION TYPE	SR PVC		
INSULATION THICKNESS	0.010		
JACKET TYPE	PVC		
JACKET THICKNESS	0.023		
NOM. CABLE OD	0.251		
VOLTAGE	600		
TEMPERATURE	-20°C to +105°C		
PUT-UP METERS	300 / 150		
WEIGHT (LBS)	62 / 31		
CSA	AWM, CMG, FT-4		
UL	CMG, UL444		
RoHS	COMPLIANT		
FLAME TEST	FT-4		
COLOUR CODE	1) Black 2) White 3) Red	4) Green 5) Orange 6) Blue	7) White/Black 8) Red/Black 9) Green/Black