

PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
3/14/2018	A	E39540	SPECIFICATION CREATED

Parent Number: FMN011-


Description: 3.0mm2 37/.32mm BC Thick Wall CU-H3XLPE

GMW15626 FL2X-A ISO 6722-1

DIAMETER: 0.156
TOLERANCE ±: 0.006

Stranding: 37/.32mm BC LHL

Style: GMW15626 CU-H3XLPE; ISO 6722-1; DIN 76722 FL2X
3.0-A T125



NOM WALL: 0.028
MINIMUM WALL: 0.022

Insulation: XLPE

Print Legend: NO PRINT

Voltage: Nominal system voltage of 60 V rms or less in automotive electrical harnesses.

Temperature: -40C to +125C

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): 32059441, 32059442, 32059443, 32059444

Approved By: R. J. H. H. H.

Date: 3/14/2018

Title: Account Manager

Company Name: IEWC



Copperfield®

1115 W. North Street
Bremen, IN 46506
Phone: 1-574-546-5115