



Specification Sheet

Lake Cable Part #: S226ST-PE

Description: 22 AWG 6 conductors 7 strands tinned copper wire, PVC insulation, shielded, and an overall PE jacket.

- 1. Conductor**
 - 1.1. AWG Size & Stranding: 22 AWG 7 Strands Class B
 - 1.2. Material: Annealed Tinned Copper
 - 1.3. Conductor Count: 6 Conductors
- 2. Insulation**
 - 2.1. Material: Polyvinylchloride
 - 2.2. Wall Thickness: 0.011"
 - 2.3. Color Code: Black, Orange, Red, Brown, Yellow, Green
- 3. Assembly**
 - 3.1. Cable Lay Length: 2.50" LHL (4.8 Tw/Ft)
 - 3.2. Shield: Aluminum/Mylar - 100% Coverage (Foil Facing Out)
 - 3.3. Drain Wire: 22 AWG 7 Strands Tinned Copper
 - 3.4. Separator: Clear Mylar Wrap - 100% Coverage
- 4. Jacket**
 - 4.1. Material: Pressure Extruded Polyethylene
 - 4.2. Wall Thickness: 0.035"
 - 4.3. Diameter: 0.225" ± 0.005"
 - 4.4. Color: Green
 - 4.5. Ripcord: N/A
 - 4.6. Weight: 37 Lbs/Mft
- 5. Markings***
 - 5.1. Type: N/A
 - 5.2. Legend: N/A
 - 5.3. Footage Markers: N/A
- 6. Standards**
 - 6.1. Cable is RoHS III compliant per Directive 2015/863/EU
 - 6.2. Maximum Operating Voltage: 300V RMS
 - 6.3. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

Date

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION