



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 bhanlon@huesonwire.com

Issue Date: 3/19/2018

Issue: 1

Construction

Description: 7/C 20 7/28TC PVC/PVC CMG		Diam. (In)
Component:	7 Conductors	
Conductor:	20 AWG 7/28 Tinned Copper to ASTM B-8	0.038"
Insulation:	0.015" Premium Grade PVC	0.068"
Color Code:	Black, White, Red, Green, Brown, Blue, Orange	0.068"
Cable Assembly:	7 Conductors Cabled	0.204"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.204"
Separator:	Non-Woven Polyester or Clear Mylar Tape 25% Overlap (optional)	0.207"
Jacket:	0.032" PVC CMG FT-4	0.271"
Jacket Color:	Gray	0.271"
Print:	E194074 20 AWG (UL) TYPE CM 75C OR AWM 2464 80C 300V --- C(UL) TYPE CMG 75C FT-4 -- ROHS	
Specifications:	<u>AWM Style</u>	<u>Temp</u>
UL	AWM-2464	80°C
Canadian cRU	AWM	80°C
		<u>Voltage</u>
		300
		<u>Flame</u>
		VW-1
		FT-1
		I/II A/B
Environmental Compliance		
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2) • REACH Regulation 169: • California Prop 65: 		
		IQ180113