

Specification Sheet

Part Number: 157-00224



Fir Tree Tie, 50lb Tensile, 8.5" Length, Panel Thickness 0.6 -6.75 mm, Black, PA66HIRHS, 500/pkg

Article Number	157-00224
Type	T50ROSFTOVAL12.5A
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• The fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more secure fit into the hole.• The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.• The oval hole fir tree fits 4 common automotive oval hole sizes.
Quantity Per	carton

Product Description

The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, the innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more secure fit into the hole.

Short Description	Fir Tree Tie, 50lb Tensile, 8.5" Length, Panel Thickness 0.6 -6.75 mm, Black, PA66HIRHS, 500/pkg
Global Part Name	T50ROSFTOVAL12.5A-PA66HIRHS-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.5
Length L (Metric)	208.3
Offset Length(Imperial)	0.49
Offset Length(Metric)	12.5
Fixation Method	Fir Tree for oval holes
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.70
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0

Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.0
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.27
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0
Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909987

Content Unit(BMEcat)

pcs.