



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 4/17/2018

Issue: 1

Construction

Description:	3/C 24 7/32 PVC/PVC AWM 2464	Diam. (In)
Component:	3 Conductors	
Conductor:	24 AWG 7/32 Tinned Copper to ASTM B-8	0.024"
Insulation:	0.01" Premium Grade PVC	0.044"
Color Code:	Brown, Blue, Black	0.044"
Assembly:	3 Conductors Cabled	0.095"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.095"
Separator:	Non-Woven Polyester or Clear Mylar Tape 25% Overlap (optional)	0.098"
Jacket:	0.032" PVC CMG FT-4	0.162"
Jacket Color:	Grey	0.162"

Print: E174416 RU AWM 2464 80C 300V 24 AWG cUL AWM IA 80C 300V OR TYPE CMG FT4
 ROHS

Specifications:	AWM Style	Temp	Voltage	Flame
UL	AWM-2464	80°C	300	VW-1
Canadian cRU	AWM	80°C	300	FT-1 I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ180177