

Specification Sheet

Lake Cable Part #: VIG162ST/M1

Description: 16 AWG 2 conductor 7 strand tinned copper with polyvinylchloride and nylon insulation, a polyvinylchloride and nylon insulated tinned copper ground conductor, an aluminum/mylar shield with a stranded tinned copper drain wire and an overall PVC jacket 600V control tray cable, approved for use in SUN RES DIR BUR 90°C applications.

1.	Conductor		
	1.1. AWG Size & Stranding: 1.2. Material:	16 AWG, 7 Strands Class B Annealed Tinned Copper	Your signature constitutes that you have read and agreed to this
	1.3. Conductor Count:	2 Conductors	specification sheet and upon
2.	Insulation		confirmation of your order; this
-	2.1. Material:	Polyvinylchloride & Nylon	item may be non-cancelable and
	2.2. Wall Thickness:	0.015" PVC & 0.005" Nylon	non-returnable.
	2.3. Color Code:	Method 1, Table E-1 + (1) Green	
	2.5. 60101 6046.	Insulated Ground	
2	Assembly	Insulated Ground	
э.	3.1. Lay Length:	3.25" LHL	Signature
	3.2. Ground:	Insulated (Green)- 16 AWG 7 Strand	
	5.2. Ground.		
		Tinned Copper	Company
	3.3. Fillers:	N/A	
	3.4. Binder:		
	3.5. Shield:	Aluminum/Mylar Tape - 100% coverage	
	3.6. Drain Wire:	18 AWG, 7 Strand Tinned Copper	Date
4.	• • • • • • •		
	4.1. Material:	Polyvinylchloride	
	4.2. Wall Thickness:	0.045"	
	4.3. Diameter:	0.294" +/- 0.025"	
	4.4. Color:	Black	
	4.5. Ripcord:	Yes	
	4.6. Cold Bend Rating:	-40°C	
	4.7. Weight:	62 lbs./Mft.	
5.	Markings		
	5.1. Type:	Cable shall be permanently identified via surface	ce inkjet print
	5.2. Legend:	LAKE CABLE E208309 16AWG 2C SHIELDED (UL) TC-ER PVC/NYLON INSULATED	
	GROUND 600V 90'C DRY/WET PVC JACKET SUN RES DIR BUR FT4 '		
		COMPLIANT" MADE IN USA	
	5.3 Footage Markers:	Vos	

5.3. Footage Markers: res

6. Standards

- 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
- 6.2. Cable is suitable for use in Class I Division II hazardous locations
- 6.3. UL listed as Type TC-ER per UL Standard 1277 for tray cables
- 6.4. UL approved for Direct Burial and Sunlight Resistant applications
- 6.5. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- 6.6. Meets ICEA S-73-532, where applicable
- 6.7. Cable is RoHS III compliant per Directive 2015/863/EU
- 6.8. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated July, 7 2017
- 6.9. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION